



BORMA WACHS[®]

Wood Professional Cosmetics



Technical data Sheet

REV 00 of 20.10.2012

LIMING WAX

DESCRIPTION:

Prepared with pure bees' and carnauba waxes, LIMING WAX nourishes and enriches every wooden surface, especially on porous woods such as ash and oak.

Thanks to its white pigments, it protects and gives an antique-decapè effect to the treated piece of furniture.

CHEMICAL/PHYSICAL CHARACTERISTICS:

Form:	paste
Colour:	coloured
Odour:	typical
Solubility:	Solwachs

HOW TO USE:

Apply the product on a support fixed and stained with Borma TURAPORI Base Coat Gel, with the aid of brush, following the wood's grain. Once the application is finished remove the material in excess with a cloth or with 0000 steel wool. Wait from 10 to 20 minutes at room temperature, and then proceed with the polishing, to enhance the pleasuring chromatic contrast on the support with the deposition of the wax in the porosity.

STORAGE:

Keep the original packaging tightly closed in a cool, ventilated place, away from flames and sparks.

PACKAGING:

The product comes in 500 mL and 5 Lt sized cans.

WARNING:

Our data sheets are prepared on the basis of average performance of our tests.

However, our technical advices are given in good faith but without any warranty.

In fact different supports, conditions of application, industrial plants, dilutions are determinant for the final result, and are often beyond our control. The user must try the product to see if it is suitable for his needs.

We will ensure the continuity of the chemical-physical properties.